





Technical Data Sheet

U-E10

COMPONENTS

The U-E10 is composed of 1 piece

CHARACTERISTICS

Weight: 0,018 kg Diameter: 149,25 mm Thickness: 1mm

MATERIAL

Material: SBR

Hardness Shore A Din 53505: 60-80 SHA

Color: Black Density: 1,55 g/cm³

Temperature range: (-30)-+70C° Tensile Strenght Din 53504: 3 Mpa Elongation at break DIN 53504: 250%

PACKAGING


Pieces per carton: 500 pcs Carton weight: 9,50 kg

Carton dimension: 400 x 290 x 150 mm

Cartons per pallet: 40 pcs Pieces per pallet: 20 000 pcs

Pallet dimensions: 100 x 120 x 220 cm





APPLICATIONS

Designed so full, half or quarter piece of the Buzon shim can be used. For use with marble, stone, granite, ceramic tiles and to obtain a better anti-slip and acoustic performance, as well as shock absorption. Use in combination with the Buzon U-E10 shim, to compensate for irregularities in the thickness of paving materials.

SAFETY INSTRUCTIONS

Buzon pedestals are designed to support external raised floors for pedestrian traffic only and are not designed to support or be subjected to moving and/or vibrating machinery & equipment, including maintenance, cleaning vehicles, automobiles and other similar equipment.